



Designed for industry and farms

LED industry and farm luminaires.

The LED luminaire is corrosion protected. Easily replaceable LED and DRIVER.

Acrylic cover. Clean-friendly and suitable for industry, agriculture and food industry, IP65.

The BASIC fixture can be easily mounted in the ceiling with stainless steel clips and push in terminals (to be performed by electrician). Ideal for new construction, as well as replacement 1 to 1, of existing fixtures - have the same dimensions.

Voltage	100 – 265 V.
Life span	50.000 hrs.
Driver	ERA0
Lumen per Watt	125
Replaceable LED+DRIVER	NO
Internal through-wiring	YES – 5 x 2,5mm ²
Cover material	Acryl - milky

Frequency	50/60 Hz
CRI / Ra	>80
LED chips	San'an
MacAdam step (SDCM)	5
Dimmable	NO
Connection	5x2x2,5mm ² Push in Terminal
Housing material	Plastic + clips in stainless steel



BASIC LED Luminaire

Item No.	Watt	Length	Kelvin (Color)	Lumen	Angle/degree	Net dimension L x W x H	Net weight
AB1120204/6	20 W	1200 mm	4000 / 6500 K	2400 lm	120°	1274 x 85 x 80 mm	1,660 kg
AB2120404/6	40 W	1200 mm	4000 / 6500 K	4800 lm	120°	1274 x 130 x 80 mm	2,080 kg
AB1150254/6	25 W	1500 mm	4000 / 6500 K	3000 lm	120°	1584 x 85 x 80 mm	2,080 kg
AB2150504/6	50 W	1500 mm	4000 / 6500 K	6000 lm	120°	1584 x 130 x 80 mm	2,600 kg

- Usually not in stock, expect delivery time

We refer to our [sales](#), [warranty](#) and [delivery terms](#) on our website.