



Designed for farms and Industry

LED Industry and farm luminaires.

Built in a strong waterproof ABS housing. The LED diodes are special coated and the driver is silicone sealed, for long durability. Ideal for installation under the Eaves. Or for example in piglet cabins. RNS System cables are available with and without rodent protection.

With RNS Plug´N Play™ system, up to 100 EASY-LIGHT can be serialized (<400W). They can easily be mounted in the ceiling and with the very low weight, they are also perfect for mounting on fixtures, machines or eaves, etc.

Voltage	100 – 265 V.
Life span	30.000 hrs.
Driver	RNS
Lumen per Watt	125
Replaceable LED + DRIVER	NO
Internal through-wiring	NO
Cover material	Polycarbonate

Frequency	50/60 Hz
CRI / Ra	>80
LED chips	EPISTAR SMD 5050
MacAdam step (SDCM)	4
Dimmable	NO
Connection	RNS plug 3 Plug´N Play™
Housing material	ABS plastic, grey



EASY-LIGHT



SEE MISCELLANEOUS ACCESSORIES AT "RNS CABLE-SYSTEMS"



Item No.	Watt	Length	Kelvin (Color)	Lumen	Angle/ degree	Net dimension	Net weight
E00427P	4 W	2700 K	480 lm	120°	Ø130 mm	0,200 kg	100
E00940P	9 W	4000 K	1080 lm	120°	Ø130 mm	0,200 kg	100

Available in special combinations against surcharge and additional delivery time

We refer to our [sales](#), [warranty](#) and [delivery terms](#) on our website.