




Designed for Farms and Industry

EX LED high bay for industry and livestock environment with Atex certification. Suitable for environments with applications of flammable and explosive chemical materials. The LED diodes are corrosion protected and the driver is 0-10V dimmable. Cleaning friendly and suitable for "high risk" industry and agriculture, waterproof - IP66. Heavy-duty, heat-dissipating housing made in cast aluminum. Atex certificering. II2G EX e mb IIC T6 Gc: zone: I-II-20-21-22-IIA-IIB-IIC CREE diodes and MEANWELL driver guarantees for the quality.

Voltage	100 – 277 V.
Life span	50.000 hrs.
Driver	MEANWELL
Lumen per Watt	130
Replacable LED + DRIVER	Only driver
Linser	
Armaturhus farve	Yellow

Frequency	50/60 Hz
CRI / Ra	>80
LED diodes	CREE JK 3030
MacAdam step (SDCM)	5
Dimmable	YES – 0-10V.
Connection	80 cm. 3G 2,5 mm ² cable
Housing material	Cast Aluminum



RNS EXPLOSION PROOF LED LUMINAIRE

Item No.	Watt	Lumen	Kelvin (color)	Dimension	Angle/Degree	Net Weight
EXA060420D	20 W	2400 lm	4000 K	662 x 107 x 61 mm	120°	2,3 kg
EXA060620D	20 W	2400 lm	5700 K	662 x 107 x 61 mm	120°	2,3 kg
EXA060440D	40 W	4800 lm	4000 K	662 x 107 x 61 mm	120°	2,4 kg
EXA060640D	40 W	4800 lm	5700 K	662 x 107 x 61 mm	120°	2,4 kg
EXA120460D	60 W	7200 lm	4000 K	1262 x 107 x 61 mm	120°	4,4 kg
EXA120606D	60 W	7200 lm	5700 K	1262 x 107 x 61 mm	120°	4,4 kg
EXA120480D	80 W	9600 lm	4000 K	1262 x 107 x 61 mm	120°	5 kg
EXA120680D	80 W	9600 lm	5700 K	1262 x 107 x 61 mm	120°	5 kg

Can be delivered with DALI dimmable, or in other special combinations against surcharge and additional delivery time.

This item is normally not a standard stock item, expect additional delivery time.

We refer to our [sales](#), [warranty](#) and [delivery terms](#) on our website.