



Designed for farms and industry

LED Industry and livestock luminaires with Plug'N Play™.

IP67 approved. Impact resistant and built in a strong aluminum profile. The LED diodes are sealed with a special coating and the driver is silicone sealed for long durability. System cables are available with and without rodent protection.

With RNS Plug'N Play™ system, up to 32 Luminaires can be connected in series (<800W). They can easily be mounted in the ceiling and with the very low weight, they are also perfect for Wire mounting or on Brackets. E.G. SOW-LIGHT™ or CONSTRUCTION-LIGHT™

Voltage	100 – 265 V.
Life span	50.000 hrs.
Driver	RNS
Lumen per Watt	125
Replaceable LED + DRIVER	YES
Internal through-wiring	YES – 3 x 1,5mm ²
Cover material	Polycarbonate

Frequency	50/60 Hz
CRI / Ra	>80
LED chips	EPISTAR SMD 5050
MacAdam step (SDCM)	3
Dimmable	NO
Connection	RNS plug 3 Plug'N Play™
Housing material	Alumium



REPLACEABLE LED 120°



OR AS 300° V – DOUBLE



MODULAR LIGHT-SYSTEM



SEE MISCELLANEOUS ACCESSORIES AT "RNS CABLE-SYSTEMS "

REPLACEABLE DRIVER



Item No.	Watt	Length	Kelvin (Color)	Lumen	Angle/degree	Net dimension L x W x H	Net weight	Max lights in a series
AM1204/618P	18 W	1200 mm	4000 / 6000 K	2250 lm	120°	1245 x 38 x 43 mm	0,840 kg	44
AM1504/625P	25 W	1500 mm	4000 / 6000 K	3125 lm	120°	1545 x 38 x 43 mm	1,050 kg	32
AMV1504/640 P (double)	40 W	1500 mm	4000 / 6000 K	5000 lm	300°	1545 x 38 x 43 mm	1,080 kg	20
AM190630P	30 W	1900 mm	6000 K	3750 lm	120°	1945 x 38 x 43 mm	1,280 kg	26
AM240640P	40 W	2400 mm	6000 K	5000 lm	120°	2445 x 38 x 43 mm	1,440 kg	20

Available in special combinations against surcharge and additional delivery time

We refer to our [sales](#), [warranty](#) and [delivery terms](#) on our website.